


## PrimaVolt™ Dimmable Drivers



- Compatible with leading edge and trailing edge TRIAC dimmers
- Short circuit and over current protection
- Dry location only (IP40)
- Air-cooled for long life operation
- Wide-range compatibility, flicker-free dimming

Item #		AL-98-03-12045	AL-98-03-24045
Output	DC Voltage	12V DC	24V DC
	Voltage Accuracy	±0.5%	±0.5%
	Rated current	3.75A	1.87A
	Rated power	45W	45W
	Minimum Load	60%	60%
Input	Voltage Range	90-135V AC / 180-250V AC	
	Frequency Range	47-63HZ	
	Power Factor (Avg.)	PF≥0.94/120V ; PF≥0.95/220V ; PF≥0.93/265V	
	Full Load Efficiency (Avg.)	>84% [12V DC]	>84% [24V DC]
	AC Current (Avg.)	0.34A/120V AC — 0.27A/220V AC — 0.24A/265V AC	
	Leakage Current	<0.25mA/120V/230V AC	
Protection	Short Circuit	Short circuit protection and autorecovery	
	Over Voltage	≤140V AC (90~135V) , ≤270V AC (170~265V)	
Environment	Working Temp. / Humidity	-40~+60°C / -40~+140°F / 20~90%RH, non-condensing	
	Storage Temp. Humidity	-40~+80°C, -40~176°F / 10~95%RH	
Safety & EMC	Safety Standards	EN-60950-1. EN-61347-1/-2/-13	
	Withstand Voltage	I/P-O/P: 3.75KV AC	
	Isolation Resistance	I/P-O/P: 100MΩ/500V DC/25°C, 77°F/70%RH	
	EMC Emission	Compliance to EN55015, EN61000-3-2 (≥50% load)	
	EMC Immunity	Compliance to EN55015; EN61000-4-2,3, 4, 5, 6, 8, 11, EN61547, a light industry level (surge4KV)	
Other	Warranty	3 Year Limited	
	Size	7.08"L x 2.36"W x 1.38"H	

1. All parameters NOT specially mentioned are measured at 110V, 230V AC input, rated load, and 25°C, 77°F of ambient temperature.

2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.