## Radialux® 2.2 Wet Location 24V RGB LED Tape Light



Field cuttable every 8 in.

Wet Location Radialux offers color-changing linear lighting for indoor and outdoor spaces that require dynamic lighting effects and dramatic accenting. With an RGB color controller, Radialux tape can change colors at your choice of speeds, or display any static color in the spectrum. Radialux 2.2 uses only 2.2 watts per foot, making it an ideal choice for small to medium spaces.

Color	RGB
Power Consumption per ft.	2.16 Watts/90mA
Input Voltage	24V DC
LED Chips per foot	9
LED Chip Spacing	1.3 in.
Tape Height	0.2 inches
Beam Angle	120°
Field Cuttable (UL 2108)	Every 8 in.
Max Run Length	16.4 feet
Dimmable	Yes (with color controller)

2			100 (111111 00101 001111 01101)			
Item #	Length	Vo	ltage	MCD /	ft. (max.)	
AL-02-01-2461	16.4 ft.	24	V DC	2	6,000	





field cuttable

• Very low energy at 2.2W per foot

- Economical
- Perfect brightness for indoor and outdoor accenting and ambient

	I
LED Chip Type	5050 SMD
Mounting	mounting clips (included)
O	100 5 1 1/00 5
Operating Temp.	-13° F to 140° F
A 11 1 =	/00 E : 40 / 0 E
Ambient Temp.	-40° F to 186° F
Constitution of the	4//6
Spool Length*	16.4 ft.
Landin	M + (ID(0) / D
Location	Wet (IP68) / Dry
0.0100.010.00	LII D IIC III 0100
Certifications	UL, RoHS, UL 2108
	/ / / / / / / / / / / / / / / / / / / /
Warranty	4 Year Limited

<sup>\*</sup>Each spool comes with 12 in. wires with female waterproof barrel plug at each end.

## Accessories (included)



All spools include 5 splice sleeves, 10 waterproof end caps, and 10 mounting clips with screws.

## Recommended Accessories\*



DMX Touch Wall Controller

AL-60-03-0003 Use with the Wireless Receiver (AL-60-03-0004 – sold separately)



Wireless Remote Controller

AL-60-03-0002 Use with the Wireless Receiver (AL-60-03-0004 – sold separately)



Receiver for Wireless Remote and DMX Touch Controllers

AL-60-03-0004



## Non-Dimmable Drivers

AL-98-04-24036	24V DC	36W
AL-98-04-24060	24V DC	60W
AL-98-04-24100	24V DC	100W
AL-98-04-24151	24V DC	151W
AL-98-04-24200	24V DC	200W

<sup>\*</sup>See our website for the full range of RGB/RGB-W controllers and accessories.