

ThruLine[™] Selector Under Cabinet LED Fixture



The ThruLine Selector LED Under Cabinet Fixture is the next generation model of Alloy's line of direct-wire ThruLine LED fixtures. Featuring a toggle switch so you can choose between 2700K and 3000K warm whites and 4000K neutral white light, this LED bar also has a premium diffusion lens for hotspot-free light. These Energy Starrated LED fixtures connect directly to AC power, with no need for external power, so installation is quick and easy. The ThruLine Selector's bright light can be dimmed with a common AC dimmer switch, or set to two brightness levels with the onboard toggle switch.

ltem #	Length	Color Temp. (Kelvins)	CRI	Watts	Diode Quantity	Lumens (max.)	Finish
AL-03-02-12001-WH	9 in.	2700K / 3000K / 4000K	94+	4W	32	200	white
AL-03-02-12011-WH	14 in.		94+	7W	36	360	white
AL-03-02-12021-WH	22 in.		94+	11W	72	610	white
AL-03-02-12031-WH	32 in.		94+	15W	108	810	white

Input Voltage	120V AC
Dimmable	With TRIAC dimmers
Width	4 inches
Height	1 inch
Housing	Aluminum
Diode Type	2835 SMD
Certs/Ratings	ETL Listed, Energy Star
Warranty	5 years



Features

- Three white color temperatures
- Two-way brightness switch
- Dimmable with TRIAC dimmers
- Aluminum housing
- Diffuser cover
- Knockouts for easy hardwiring
- Includes cable connector and interconnector plug



Accessories

One interconnector and wire connector harness is included with each fixture. Other accessories (sold separately) are: AC Power Cable to connect a fixture to an outlet, AC Splice Cable to hardwire a fixture to power, and Interconnector Cables for connecting fixtures together.



AC Splice Cable (sold separately) AL-03-01-9951-WH - (6 foot - white) AL-03-01-9952-BL - (6 foot - black)

AC Power Cable (sold separately) AL-03-01-9901-WH - (6 foot - white) AL-03-01-9912-BL - (6 foot - black)



Interconnector and wire connector (included)





Interconnector Cable (sold separately) AL-03-01-9921-WH - (12 inch - white) AL-03-01-9922-BL - (12 inch - black) AL-03-01-9931-WH - (36 inch - white) AL-03-01-9932-BL - (36 inch - black)


www.AlloyLED.com / solutions@AlloyLED.com / 800.910.LEDS (5337)

ALLOY $L \equiv D^{\circ}$


2700K









3000K







												91
	_									<u></u> Ra) =	<mark>93</mark> 94
R1	_	_	_	_	_	_	_	_	_			
R2												98
R3												98
R4												93
R5												94
R6												96
R7												92
R8				_		_		_				83
R9												64
R10												93
R11												93
R12												85
R13												95
R14												99
R15												91
	0	10	20	30	40	50	60	70	80	90	100)

4000K







www.AlloyLED.com / solutions@AlloyLED.com / 800.910.LEDS (5337)