



TECHNICAL DATA

| Model            | Volt | Color Temperature | Watts per meter/ foot | Lumen Output per meter/ per foot | Beam Angle | Diodes per meter/ foot | Chip Type    | CRI | Max run length (meter/ feet) |
|------------------|------|-------------------|-----------------------|----------------------------------|------------|------------------------|--------------|-----|------------------------------|
| WP-K-22-1220-24V | 24   | 2200              | 9.6W/M 3W/F           | 520L/M 158L/F                    | 120°       | 120/M 38/F             | Epistar 3528 | 90+ | 32/ 10 m                     |
| WP-K-25-1220-24V |      | 2500              |                       | 623L/M 189L/F                    |            |                        |              |     |                              |
| WP-K-27-1220-24V |      | 2700              |                       | 635L/M 194L/F                    |            |                        |              |     |                              |
| WP-K-30-1220-24V |      | 3000              |                       | 660L/M 201L/F                    |            |                        |              |     |                              |
| WP-K-35-1220-24V |      | 3500              |                       | 685L/M 209L/F                    |            |                        |              |     |                              |
| WP-K-40-1220-24V |      | 4000              |                       | 715L/M 218L/F                    |            |                        |              |     |                              |
| WP-K-50-1220-24V |      | 5000              |                       | 702L/M 214L/F                    |            |                        |              |     |                              |



WIRE OPTIONS

36"-72" wire leads (20 gauge jacketed wire)

