

Dimmable Drivers with Junction Box



This dimmable driver is housed within a code-compliant junction box for use in dry and wet indoor and outdoor locations. Compatible with MLV and incandescent dimmers (See Alloy LED's Dimmer Compatibility List for details.) These drivers are already derated, which means they can be loaded to maximum wattage capacity.

- Compact aluminum case
- NEMA 3R housing is rated for outdoor use
- Auto-Reset Protection for short circuits
- Over-voltage and over-temperature protection
- UL 8750



Item #	AL-98-02-24096	
Output	Output Voltage	24V DC
	Max. Load	96W
	Output Current Max. Load	4.2A
	Efficiency (Avg.)	>90%
	Power Factor	0.95
Input	Input Voltage	120V AC
	Input Current at Max. Load	1A
Environment	Operating Temp.	-20°C - 70°C (-4°F - 158°F)
Safety	Short Circuit Protection	Yes
	Over Current	Yes
	Over Temperature	Yes
	Open Circuit Protection	Yes
	Housing	NEMA 3R
	Standards	UL 8750
Dimming	Min. Load (on/off switch)	none
	Min. Load (dimmer switch)	8W
Other	Input Wires (White \ Black)	14 AWG
	Output Wires (Red \ Black)	18 AWG
	Dimensions	6.77 in. x 2.67 in. x 1.26 in.
	Weight	17 oz.
	Warranty	5 years