


## PrimaVolt™ Dimmable Drivers



### Features:

- Short circuit and over current protection
- Dry/wet location (IP67)
- Air-cooled for long life operation
- Compatible with leading edge and trailing edge TRIAC dimmers
- Wide-range compatibility, flicker-free dimming
- UL Compliant with Class 2 power supplies



Item #	AL-98-03-24150	
Output	DC Voltage	24V DC
	Voltage Accuracy	±0.5V
	Rated current	6.25A
	Rated power	150W
	Minimum Load	60%
Input	Voltage Range	100~135V AC/170~265V AC
	Frequency Range	47~63HZ
	Power Factor (Avg.)	≥0.75/110V ; ≥0.8/220V
	Full Load Efficiency (Avg.)	>86% (24V DC)
	AC Current (Avg.)	0.6A/110V AC — 0.7A/220V AC
	Leakage Current	<0.25mA/110V/220V AC
Protection	Short Circuit	Short circuit protection and autorecovery
	Over Voltage	≤120%
Environment	Working Temp. / Humidity	-40~+60°C / -40~+140°F
	Storage Temp. Humidity	-40~+80°C, -40~176°F / 10~95%RH
Safety & EMC	Safety Standards	EN-60950-1, EN61347-1 EN61347-2-13
	Withstand Voltage	I/P-O/P: 3.75KV AC I/P-FG: 1.88KV AC O/P-FG: 0.5K VAC
	Isolation Resistance	I/P-O/P: 100MΩ/500V DC/25°C, 77°F/70%RH
	EMC Emission	Compliance to EN55015, EN61000-3-2 (≥50% load)
	EMC Immunity	Compliance to EN55015; EN61000-4-2,3, 4, 5, 6, 8, 11, EN61547, a light industry level (surge4KV)
Other	Warranty	3 Year Limited
	Size	8.92"L x 3"W x 1.85"H

1. All parameters NOT specially mentioned are measured at 110V, 230V AC input, rated load, and 25°C, 77°F of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.

## Optional Accessory

Dedicated junction boxes designed to fit specific PrimaVolt models.

Item #	Use with PrimaVolt models
AL-98-03-9904	150W, 200W

