


ALLOYLED®

Radialux® 4.4 24V RGB LED Tape Light



cut point every 4 in.

Radialux offers color-changing linear lighting for any space that requires dynamic lighting effects and dramatic accenting. With the use of an RGB color controller, Radialux tape lights can change colors at your choice of speeds or display any static color in the spectrum. Radialux 4.4 provides high-output color-changing lighting for medium applications, retail, and hospitality spaces.

- Perfect brightness for medium applications, retail, and hospitality spaces
- Low profile is ideal for indirect lighting and reveals
- Saturated colors

Color	RGB
Power Consumption per ft.	4.32 Watts/180mA
Input Voltage	24V DC
LED Chips per foot	18
LED Chip Spacing	0.65 inches
Tape Height	0.1 inches
Beam Angle	120°
Field Cuttable (UL 2108)	4 in.
Max Run Length	16.4 feet
Dimmable	Yes (with color controller)

LED Chip Type	5050 SMD
Mounting	3M™ Self-Adhesive Tape (non-porous)
Operating Temp.	-13° F to 140° F
Ambient Temp.	-40° F to 186° F
Spool Lengths*	16.4 ft., 50 ft., and 100 ft.
Location	Indoor, Dry
Certifications	UL, RoHS, UL 2108
Warranty	4 Year Limited

*Each spool comes with 36 in. lead wires at each end.

Item #	Length	Voltage	MCD / ft. (max.)
AL-02-02-2401	16.4 ft.	24V DC	61,040
AL-02-02-2421	50 ft.	24V DC	
AL-02-02-2441	100 ft.	24V DC	



field cuttable

Recommended Accessories*



DMX Touch Wall Controller

AL-60-03-0003
Use with the Wireless Receiver (AL-60-03-0004 – sold separately)



Wireless Remote Controller

AL-60-03-0002
Use with the Wireless Receiver (AL-60-03-0004 – sold separately)



Receiver for Wireless Remote and DMX Touch Controllers

AL-60-03-0004



Non-Dimmable Drivers

AL-98-04-24036	24V DC	36W
AL-98-04-24060	24V DC	60W
AL-98-04-24100	24V DC	100W
AL-98-04-24151	24V DC	151W
AL-98-04-24200	24V DC	200W

*See our website for the full range of RGB/RGB-W controllers and accessories.