


Flexible LED Strip 9.6 Watt / M, IP 65



Product code No.	Color Temp.	Watts/ Meter Watts/ Foot	LEDs/ Meter LEDs/ Foot	Lumens / Meter Lumens/ Foot	CRI	LED Chip Type	Beam Angle	Input Voltage
WP-K-27-1220	2700K	9.6 W/M 3 W/F	120 LEDs/M 38 LEDs/F	635 L/M 200 L/F	90+	Epistar 3528	140°	12V
WP-K-30-1220	3000K	9.6 W/M 3 W/F	120 LEDs/M 38 LEDs/F	750 L/M 230 L/F	90+	Epistar 3528	140°	12V
WP-K-35-1220	3500K	9.6 W/M 3 W/F	120 LEDs/M 38 LEDs/F	800 L/M 250 L/F	90+	Epistar 3528	140°	12V
WP-K-40-1220	4000K	9.6 W/M 3 W/F	120 LEDs/M 38 LEDs/F	845 L/M 265 L/F	90+	Epistar 3528	140°	12V

-22°F to 122°F
OPERATING TEMPERATURE

IP65
IP

~~LEAD
MERCURY~~
CONTENT

12V DC
POWER OUT

DIMMABLE

OUTDOOR

~~UV
IR~~
RADIATION

CE


E

RoHS
COMPLIANT

Water and dust resistant – IP 65

Protects against:

- Rain and humidity
- Water splash
- Dust and dirt
- Water jets
- Particles



Wire options:

36"-72" wire leads (20 gauge jacketed wire)

