

WP-K-CR-1820-HD-24V FLEXIBLE LED STRIP DATA SHEET

- UL Listed
- CRI 95+
- 2-Step MacAdam's ellipse, single benning
- L70- Over 50,000 hours
- R9 up to 97
- Reverse voltage protection
- Minimum 2oz copper PCB



TECHNICAL DATA

Model	Chip	IP protection	Power consumption	Color temperature	Lumen output	Diode QTY per foot	Input voltage	Beam Angle	Max run length	LED width
WP-K-CR-22-1820-HD-24V	Epistar 2016	IP 65 (silicon sleeve)	5.6 W/ft	2200 К	301 lm/ft	81 pcs/ft	24 V	120 °	16'	12 mm
WP-K-CR-25-1820-HD-24V	Epistar 2016	IP 65 (silicon sleeve)	5.6 W/ft	2500 K	404 lm/ft	81 pcs/ft	24 V	120 °	16'	12 mm
WP-K-CR-27-1820-HD-24V	Epistar 2016	IP 65 (silicon sleeve)	5.6 W/ft	2700 k	367 lm/ft	81 pcs/ft	24 V	120 °	16'	12 mm
WP-K-CR-30-1820-HD-24V	Epistar 2016	IP 65 (silicon sleeve)	5.6 W/ft	3000 K	438 lm/ft	81 pcs/ft	24 V	120 °	16'	12 mm
WP-K-CR-35-1820-HD-24V	Epistar 2016	IP 65 (silicon sleeve)	5.6 W/ft	3500 K	448 lm/ft	81 pcs/ft	24 V	120 °	16'	12 mm
WP-K-CR-40-1820-HD-24V	Epistar 2016	IP 65 (silicon sleeve)	5.6 W/ft	4000 K	470 lm/ft	81 pcs/ft	24 V	120 °	16'	12 mm
WP-K-CR-50-1820-HD-24V	Epistar 2016	IP 65 (silicon sleeve)	5.6 W/ft	5000 K	413 lm/ft	81 pcs/ft	24 V	120 °	16'	12 mm



WP-K-CR-1820-HD-24V FLEXIBLE LED STRIP DATA SHEET

RELATED EXTRUSIONS



DES Extrusion Ref: 18030ANODA



Ref: 18014ANODA



IKON Extrusion Ref: 18013ANODA

Ref:



IMET Extrusion 18012ANODA



JAZ Extrusion Ref: B8547ANODA



KIDES Extrusion Ref: 18031ANODA

LESTO Extrusion

B5551ANODA

Ref:



KIDES-DUO Extrusion Ref: 18032ANODA



KOPRO Extrusion Ref: B6367ANODA



Extrusion Ref: B7890ANODA

KOZEL Extrusion Ref: B6454



KOZUS Extrusion



Ref: B5552ANODA



SEKOMA Extrusion Ref: B6595ANODA



LIPOD Extrusion

B5554ANODA

Ref:

SEPOD Extrusion Ref: B6593ANODA



18015ANODA

Ref:

Ref:



Extrusion B5553ANODA Ref:















SILER Extrusion B9325ANODA Ref:

STEPUS Extrusion 18038ANODA