

NHRMIC-926LMRAT

6" IC Air-Tight LED Dedicated Sloped Remodel Housing (Compatible with Marquise I Sloped Series)

PRODUCT DESCRIPTION

Dedicated remodel housing for sloped ceiling with a 6/12 pitch ceiling. Air-tight housing additionally reduces energy costs by decreasing the flow or air escaping through the ceiling. Rated for direct contact with insulation and adjacent ceiling structures. The housing is dedicated and labeled for use with Marquise I sloped fixtures.

FEATURES

- IC rated for direct contact with insulation
- Quick connect provided for electrical connection to the LED reflectors
- ASTM E283 for Air-Tight
- 24-1/2" bar hangers with captive nails and alignment foot

CONSTRUCTION

Housing: 0.040 steel housing terminates at a 1/4" ceiling flange for even positioning of housing angle within the ceiling. Structural arm consists of 0.050 steel and connects to housing with junction box. Integral spring brackets provided.

Air Flow Restriction: Housing has factory installed gaskets to restrict airflow from room into ceiling plenum to <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

Clearance*: "IC" Insulated ceiling housings are direct contact rated. **Not to be used in direct contact with spray foam insulation.**

Junction Box: Prewired 25 cubic inch 0.064" thick galvanized steel, with five 1/2", two 3/4" knockouts, four Romex[®] pryouts, and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Through branch circuit wiring, (4-in, 4-out).

Mounting:

Four high tension tempered steel springs secure remodel housing to 5/8" thick (max) ceiling (Hole cutout template provided for convenience).

ELECTRICAL

Input Voltage: 120V

Operating Temp.: 122°F (50°C) max. ambient temp. (with suitable reflectors)

Dimming: Triac or ELV dimming

Click Here or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

EMERGENCY (NEPK-BSL17C-C2U)

Remote 90-minute battery back-up and remote test switch can be specified and installed separately.

COMPATIBLE REFLECTORS


CATALOG NO.	DESCRIPTION
NRMC-6S11	6" Sloped Open Reflector
NRMC-6S12	6" Sloped Baffle

LABELS AND LISTINGS


- cULus Listed for Damp Location w/ Feed Through (wet location when used with compatible reflectors)
- Meets or exceeds ASTM-283 Air-Tight Requirements



PRODUCT IMAGES AND DIMENSIONS



6-1/2" x 7"
Elliptical Cut-Out



6" IC Air-Tight LED Dedicated Sloped Remodel Housing - Compatible with Marquise I Slope Reflectors

Installation Type

NHRMIC-926LMRAT = 6" Remodel

Example: NHRMIC-926LMRAT = 6" IC Air-Tight LED Dedicated Sloped Remodel Housing